





GENERAL SPECIFICATION SHEET FOR REFERENCES



WT8060, WT10060,

WT14060, WT8070,

WT14070, WT18070

KEA

SINKS

SU1B60, SU1B70, SU2B140, SU2B200, PW1B, PW2B



SHELVING UNITS

SWS-15030, SWS-18030, DWS-15030, DWS-18030, 4TS9050 , 4TS15050 , 4TS18050

- 1. General features
- Material: High-grade AISI 304 stainless steel for superior durability and corrosion resistance.
- Construction: Fully welded and reinforced for maximum stability.
- Surface Finish: Brushed stainless steel for easy cleaning and a professional appearance.
- Adjustability: Height-adjustable feet for leveling on uneven surfaces.
- Assembly: Ready to assemble, all products are delivered flat-packed for easy transport and storage.
- 2. Top & shelf thicknesses
- Worktable Tops: 1.5 mm to 2.0 mm thick, reinforced with a sound-deadening underlay.
- Undershelves: 1.0 mm to 1.5 mm thick, depending on model.
- Wall Shelves: 1.0 mm thick with heavy-duty wall brackets for secure mounting.
- Freestanding Shelving Units: 1.2 mm thick shelves with 38 mm stainless steel posts.

3. Available products

- Tables: Worktables with/without undershelves, wall-mounted and central models. •
- Sinks: Single, double, and pot-wash sinks with different configurations. .
- Shelving Units: Wall-mounted, freestanding, stainless steel, and chrome-coated models.

4. Key benefits

- Hygiene Compliance: Meets food safety and HACCP standards. •
- Heavy-Duty Design: Built for high-traffic commercial kitchens.
- Customizable Options: Available in multiple sizes and configurations. •
- Easy Maintenance: Resistant to stains, rust, and harsh cleaning agents.
- Efficient Transport & Storage: Delivered flat-packed ("à plat"), making shipping and handling easier. ٠

5. Applications

Restaurants, hotels, catering services, food production facilities, and industrial kitchens.

6. Assembly guidelines

Step 1:

Lay the top of the table upside down on a soft surface to prevent scratches.

Remove the "black" leg caps from the sockets and discard.

Insert one of the legs into the table socket and tighten the

allen/hex screws. Repeat for the


Step 2:

Slide the shelf into the height desired and tighten the allen/hex screws.

Step 3:

Snap the gray plastic feet into the bottom of each leg.

Turn the table over. Adjust the feet to level table.



Note:

To adjust the shelf height, simply loosen the allen/hex screws, move the position of the shelf and retighten.