



TABLE TOP REFRIGERATOR

TKSA-TTR15080D

STANDARD FEATURES

Dual Temperature

- ✓ Switch modes with confidence: dial 0–10 °C for mise en place or flip to –18 to –6 °C for deep-freeze—one bench does both, so you adapt service without changing stations.
- ✓ 80 cm full-width, two-door access speeds loading and picking during the rush; adjustable shelving lets you stage GN pans or bulk packs exactly how your prep line flows.
- ✓ Engineered for tough kitchens: Climatic Class 4 keeps temperatures stable with frequent openings; R290 (56 g) delivers strong pull-down with low GWP and fast recovery.
- ✓ Plug-and-play efficiency on a standard outlet—196 W / 2.5 A, 220 V-50 Hz—keeps energy use lean while protecting your product quality.
- ✓ Built for hygiene and longevity: food-grade AISI 304 stainless steel inside and out, heavy-duty castors for easy under-unit cleaning, and Protective Class I earthing for safety and compliance.



PRODUCT SPECIFICATIONS

Dimensions	150 x 80 x 85 cm
Temperature	-18 to +10 °C
Volume	500 L
Rated current	2,5 A
Refrigerant/Mass	R290 / 56 g
Energy source	220 V / 50 Hz
Foaming agent	C5H10