





## **TABLE TOP** REFRIGERATOR

## TKSA-TTR18080D

## STANDARD FEATURES

**Dual Temperature** 

- ✓ Switch modes with confidence: dial 0–10 °C for mise en place or flip to -18 to -6 °C for deep-freeze—one bench does both, so you adapt service without changing stations.
- ✓ 80 cm full-width, two-door access speeds loading and picking during the rush: adjustable shelving lets you stage GN pans or bulk packs exactly how your prep line flows.
- ✓ Engineered for tough kitchens: Climatic Class 4 keeps temperatures stable with frequent openings; R290 (65 g) delivers strong pull-down with low GWP and fast recovery.
- ✓ Plug-and-play efficiency on a standard outlet—235 W / 2.5 A, 220 V-50 Hz—keeps energy use lean while protecting your product quality.
- ✓ Built for hygiene and longevity: food-grade AISI 304 stainless steel inside and out, heavy-duty castors for easy under-unit cleaning, and Protective Class I earthing for safety and compliance.



## PRODUCT SPECIFICATIONS

Dimensions	180 x 80 x 85 cm
Temperature	-18 to +10 °C
Volume	600 L
Rated current	2,5 A
Refrigerant/Mass	R290 / 65 g
Energy source	220 V / 50 Hz
Foaming agent	C5H10